

# smartMODUL<sup>BASIC</sup> // Technical Data

Infrared gas sensor for diffusion with digital interfaces



Infrared gas sensor using dual beam technology, with measurement and reference channel, for monitoring room air and process control applications. Integrated evaluation electronics for drift and temperature compensation.

- Infrared measuring principle (NDIR)
- Dual beam technology
- Modbus ASCII via UART
- Temperature compensation
- Gas entry by diffusion
- High selectivity

Gases *	Measurement range	Model type
acetylene $C_2H_2$	0-2.3 Vol.-% (0-100 % LEL)	B1-010236-00000
ammonia $NH_3$	0-3.5 Vol.-%	B1-200356-00000
n-butane $C_4H_{10}$	0-1.4 Vol.-% (0-100 % LEL)	B1-020146-00000
ethylene $C_2H_4$	0-2.4 Vol.-% (0-100 % LEL)	B1-030246-00000
	0-2000 ppm	B1-030205-00000
carbon dioxide $CO_2$	0-5000 ppm (0-100 % TLV)	B1-212505-00000
	0-5 Vol.-%	B1-212506-00000
	0-20 Vol.-%	B1-212207-00000
carbon monoxide $CO$	0-2 Vol.-%	B1-221206-00000
methane $CH_4$	0-4.4 Vol.-% (0-100 % LEL)	B1-040446-00000
propane $C_3H_8$	0-1.7 Vol.-% (0-100 % LEL)	B1-050176-00000
sulphur hexafluoride $SF_6$	0-1000 ppm (0-100 % TLV)	B1-600105-00000
dichlorotrifluoroethane $R123$	0-2000 ppm	B1-730205-00000
pentafluoroethane $R125$	0-2000 ppm	B1-720205-00000
tetrafluoroethane $R134a$	0-2000 ppm	B1-710205-00000
refrigerant $R404a$	0-2000 ppm	B1-740205-00000
chlorodifluoromethane $R22$	0-2000 ppm	B1-700205-00000

\* More gases and measuring ranges on request

Sensors similar to the illustration

# smartMODUL<sup>BASIC</sup> // Technical Data

Infrared gas sensor for diffusion with digital interfaces

General features	
Measurement principle:	Non Dispersive Infra-Red (NDIR), dual wavelength
Measurement range:	dependent on model – see list
Gas supply:	by diffusion
Dimensions:	62 mm x 37 mm x 30 mm (L x W x H)
Technical features @ 25°C, 1013 mbar	
Response time (t <sub>90</sub> ):	Appr. 30 s
Resolution:	1 ppm to 0.01 Vol.% FS <sup>1</sup>
Accuracy:	≤ ±2 % FS <sup>1</sup>
Long term stability (zero):	≤ ±2 % FS <sup>1</sup> over 12 month period
Long term stability (span):	≤ ±2 % FS <sup>1</sup> over 12 month period
Repeatability:	≤ ±2 % FS <sup>1</sup>
Linearity error:	≤ ±1 % FS <sup>1</sup>
Lower detection limit:	≤ 1 % FS <sup>1</sup> (typically)
Operating temperature:	-10 °C to 40 °C
Storage temperature:	-20 °C to 60 °C
Humidity:	0 % to 95 % rel. humidity (not condensing)
Temp. dependence (zero):	≤ ±0.01 % FS <sup>1</sup> per °C
Temp. dependence (span):	≤ ±0.2 % FS <sup>1</sup> per °C
Air pressure:	950 to 1050 mbar
Pressure dependence (zero):	-
Pressure dependence (span):	0.1 % to 0.2 % per mbar <sup>2</sup>
Warm-up time:	< 2 minutes (start up time) < 30 minutes (full specification)
Communication	
Digital output signal:	Modbus ASCII via UART
Electrical data	
Supply voltage:	5 V DC ± 5 % or 6 V DC ± 5 % (model dependent)
Supply current:	70 mA average, max. 140 mA
Power consumption:	< 1 Watt

<sup>1</sup> FS = Full scale | <sup>2</sup> Dependent on the gas and the measurement range

Please consult smartGAS Marketing for parts specified with other temperature and measurement ranges.

At first initiation and depending on application and ambient conditions recalibration is recommended. Recurring cycles of recalibration are recommended.

All rights reserved. Any logos and/or product names are trademarks of smartGAS. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of smartGAS is strictly prohibited. All specifications – technical included – are subject to change without notice. Depending on the application, the target gas and the measurement range the technical data may differ. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale.

For more information, please visit [www.smartGAS.eu](http://www.smartGAS.eu) or contact us at [sales@smartgas.eu](mailto:sales@smartgas.eu)